

## A: Datasheet

Algorithm: kneron\_001

Developer: Kneron

Submission Date: 2021\_06\_10

Template size: 2048 bytes

Template time (2.5 percentile): 455 msec

Template time (median): 472 msec

Template time (97.5 percentile): 476 msec

Investigation:

Frontal mugshot ranking 192 (out of 279) -- FNIR(1600000, 0, 1) = 0.0295 vs. lowest 0.0009 from sensetime\_005

Mugshot webcam ranking 233 (out of 241) -- FNIR(1600000, 0, 1) = 0.6209 vs. lowest 0.0062 from sensetime\_005

Mugshot profile ranking 28 (out of 210) -- FNIR(1600000, 0, 1) = 0.2369 vs. lowest 0.0587 from xforwardai\_002

Immigration visa–border ranking 127 (out of 168) -- FNIR(1600000, 0, 1) = 0.1441 vs. lowest 0.0013 from visionlabs\_010

Immigration visa–kiosk ranking 112 (out of 165) -- FNIR(1600000, 0, 1) = 0.2797 vs. lowest 0.0568 from cloudwalk\_hr\_000

Identification:


Frontal mugshot ranking 278 (out of 279) -- FNIR(1600000, T, L+1) = 0.9998, FPIR=0.001000 vs. lowest 0.0018 from sensetime\_004

Mugshot profile ranking 187 (out of 209) -- FNIR(1600000, T, L+1) = 0.9999, FPIR=0.001000 vs. lowest 0.1331 from cloudwalk\_hr\_000


Immigration visa–border ranking 162 (out of 167) -- FNIR(1600000, T, L+1) = 1.0000, FPIR=0.001000 vs. lowest 0.0047 from idemia\_008

Immigration visa–kiosk ranking 154 (out of 162) -- FNIR(1600000, T, L+1) = 1.0000, FPIR=0.001000 vs. lowest 0.0996 from cloudwalk\_hr\_000


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (sensetime\_004)



### C: Evolution of accuracy for KNERON algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images


N 00640000 01600000



F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects




### H: Reduced length candidate lists for human review

Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




# I: FNIR and FPIR dependence on threshold


Dataset is border-border with time-lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime\_005)




L: Investigational mode: FNIR(1600000, R, 0) by probe type



M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements.  
The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations




O: FNIR(T, N = 1.6 million) by sex, age and time-lapse. The top row gives investigational rank-1 miss rates.  
 The bottom panels give high threshold for more lights-out identification with low FPIR.



P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.

Algorithm: kneron\_001, Dataset: Border–Crossing Ageing  
Threshold: 1.000000 set to achieve FPIR(30–45, Male) = 0.001



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801

